

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053992 A2

(51) International Patent Classification⁷: **B60K 41/00**

(21) International Application Number:
PCT/JP2004/018446

(22) International Filing Date: 3 December 2004 (03.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-407549 5 December 2003 (05.12.2003) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **INAGAKI, Shoji** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(74) Agent: **ITEC INTERNATIONAL PATENT FIRM**; Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku, Nagoya-shi, Aichi, 4600008 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AUTOMOBILE AND CONTROL METHOD OF AUTOMOBILE



(57) Abstract: In an automobile of the invention, a cornering drag estimator 61 estimates a cornering drag from measurements of steering angle and vehicle speed V. A gain multiplier 62 multiplies the estimated cornering drag by a preset gain K to reduce the estimated cornering drag. A phase adjuster 63 adjusts the phase of the rest of the estimated and reduced cornering drag. An implementation system 70 receives the sum of the output of the gain multiplier 62 and the output of the phase adjuster 63 and regulates the throttle opening of an engine according to the received sum. This adjusts the phase and the degree of reduction of the estimated cornering drag. This arrangement of the invention attains the adequate levels of pitching and rolling, which may be caused in the vehicle in the turning state.

WO 2005/053992 A2